



PRODUCT SUBMITTAL SHEET

For more information or questions, please contact:
info@dragonboard.com
(732) 662-6275

DragonBoard™ MAG X-24 Structural Subfloor Panel (3/4" nominal)

DragonBoard™ MAG X-24 is a high-performance structural sub-floor panel developed for wide-span and premium flooring applications. It is designed as an alternative to traditional gypcrete-topped OSB and plywood subfloor systems, as well as metal deck and concrete floor systems, in multifamily and other low-rise commercial construction. MAG X-24 provides a durable, termite-, mold-, and moisture-resistant solution for fire-rated floor assemblies while delivering excellent dimensional stability and reliable long-term performance throughout construction and over the life of the building.

Product Specifications	
Thickness	3/4 in. nominal (18mm)
Panel Width	48 in. (4') Square Edge
Panel Length	96 in. (8') Shiplap Edge
Panels Per Pallet	22
Weight	4.53 lbs. per sq. ft.
Weight Per Panel	Approx. 145 lbs.
Pallet Weight	3,190 lbs.

Board Capacity (PSF)			
Spacing o.c.	L/360 Dry	L/360 Wet	Strength Limit 3.0x Safety Factor Dry / Wet
16"	497	366	643 / 521
19.2"	287	212	446 / 362
24"	147	108	286 / 231

Table Notes:

- Preliminary engineering values based on Intertek Report No. 250218008SHF-002 and ASTM
- C1185-23, Section 5.
- Dry MOR/MOE: 5,120 psi / 1,183 ksi. Wet MOR/MOE: 4,148 psi / 871 ksi.
- L/360 values are for three-span continuous panels. Strength-limit values are reduced by a 3.0
- safety factor (MOR/3); deflection governs in every case.

Typical Applications:

- Multifamily construction
- Modular and offsite construction
- Hotels and hospitality
- Senior living facilities
- Student housing and dormitories
- Healthcare facilities

Performance Features:

- 1- and 2-hour fire-rated assemblies
- Moisture resistant
- Mold resistant
- Termite resistant
- High dimensional stability
- Highest flexural strength and surface durability



Product Installation:

- Installs over wood or steel trusses and joists
- Installs without the need for specialized tools

DragonBoard™ Codes & Standards:

- International Building Code (IBC): 2006 – 2024
- Fire Testing Per ASTM E84, E136, E119
 - UL Fire Rated Assemblies:
 - UL G575 (1 and 2-Hour Fire-Resistance Steel Assembly)
 - UL L583 (1-Hour Fire-Rated Wood Assembly)
- Diaphragm ASTM E455
- Sound: ASTM E90, E492
- Mold Resistance: ASTM G21
- Extreme Termite Resistance: ADWPA E-1-13
- Moisture Resistance: ASTM C1185
- Flexural Strength/Modulus of Rupture ASTM C1185
- Does not contain Asbestos, Formaldehyde, or VOC's

***Environmental Stewardship: DragonBoard™ USA supports the programs of the United States Green Building Council (USGCB).**